



**PRODUCT SPECIFICATION | Classic Kitchen
Crawford Mobile Commercial Kitchen**

Classic Kitchen	
Dimensions	
Folded <ul style="list-style-type: none"> • Mobile transportable transforming building (ISO compliant) • L 6052mm x W 2440mm x H 2890mm 	Open <ul style="list-style-type: none"> • L 6052mm x W 3815mm x H 2890mm
Weight – Fully Packed	
<ul style="list-style-type: none"> • 6,000kg to 7,000 approximately – depending on customised Equipment specification 	
Technical Aspects, Safety & Compliance	
Plumbing <ul style="list-style-type: none"> • All gas and electrical equipment fully tested prior to hire – Industry Best Practice (exceeding minimum Energy Safe Victoria requirement) • Gas Manifold Systems Energy Safe Compliant using certified components within AS/NZS5601 • 1x 19mm MI water inlet • 1x flexible connect self-sealing LPG inlet • 1x 25mm cam lock grey water outlet • 1x waste water tank (sullage) • 1x grey water pump lift 5m • 1x Rinnai instantaneous LPG hot water service • 1x gas manifold to suit connection of 4 x 45kg LPG cylinders Electrical <ul style="list-style-type: none"> • Compliant with Energy Safe Victoria requirements using certified components under AS3000/3001 • 2x 32 amp 5-pin 3 phase inlet • 1x circuit board with RCD protection Annex Extension Area <ul style="list-style-type: none"> • 2x Service hatches • LED Strip lighting • Multicell UV block polycarbonate roof Other <ul style="list-style-type: none"> • During transportation Kitchens comply with ISO and Road Transportation requirements • Low to the ground, trolley suitable (OH&S compliant) – ramps by arrangement 	Inside Kitchen <ul style="list-style-type: none"> • Commercial food grade finishes • LED Lighting • 2x reverse cycle air conditioners • 1x extraction canopy with grease filters • 1x hand wash basin • 1x 600x400x200 sink with commercial tapware • 1x 32 amp 3 phase outlet • 2x 15 amp outlets • 6x double power points • Slip resistant commercial grade floor covering • 1x fire blanket • 1x fire extinguisher Equipment & Appliances <ul style="list-style-type: none"> • Appliances supplied within Manufacturer’s specifications and installed within appropriate ESV and ventilation/combustion tolerance ratios and clearance requirements • 1x pass thru dishwasher (2 baskets) • 1x twin basket deep fryer • 1x 600mm flat top grill • 1x 4 Burner cooktop with Oven under • 2x stainless steel folding work benches

Signage, Badging, Wrapping

- Crawford Kitchens can be wrapped and have custom signage affixed by arrangement

Site Requirements

- Sufficient access at site for swing loading trucks (8m x 8m); Maximum fall (slope) of 600mm over 6m; Overhead no lower than 4.4m. Site review may be required to ensure suitable space/access
- Power requirement – 2x 32 AMP (3 phase) power supply within 10m of kitchen placement
- Availability of fresh potable water supply within 10m of kitchen
- Legal discharge point for sullage (waste water) within 10m of kitchen
- Room for 4 x 45kg Gas Bottles to attach to Kitchen exterior depending on customer configuration and requirements at time of hire

Photographs

